

VAMOOTS RSL

FRAME SIZE [CM]	EFFECTIVE TOP TUBE [CM]	SEAT TUBE /C-T/ [CM]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB DROP [CM]	CHAIN STAY LENGTH [CM]	STAND-OVER [IN]	TOP TUBE SLOPE	FORK RAKE [MM]	STACK	REACH
48	51.5	45.0	10.0	72.50	74.75	7.4	40.5	28.5	11.1	50	535	369
50	52.5	46.0	10.5	72.75	74.50	7.4	40.5	28.8	10.4	50	541	375
52	53.5	47.0	11.5	73.00	74.25	7.3	40.5	29.2	10.5	45	552	380
54	54.5	48.0	12.5	73.25	74.00	7.2	40.5	29.6	10.3	45	561	385
55	55.5	49.0	13.5	73.50	73.50	7.2	40.7	30.0	10.2	45	571	387
56	56.5	50.0	14.5	73.50	73.25	7.2	40.7	30.4	10.1	45	581	391
58	57.5	51.5	16.0	73.75	73.00	7.1	41.0	30.9	10.3	40	597	394
60	58.5	53.0	17.5	74.00	73.00	7.0	41.0	31.6	10.0	40	611	399
62	59.5	55.0	19.5	74.25	72.50	6.8	41.5	32.3	9.9	40	629	398

STANDOVER MEASURED WITH 23C TIRE / MAX TIRE WIDTH 27MM / STACK AND REACH INCLUDE CK INSET UPPER CUP AND RACE



VAMOOTS CR

FRAME SIZE [CM]	EFFECTIVE TOP TUBE [CM]	SEAT TUBE /C-T/ [CM]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB DROP [CM]	CHAIN STAY LENGTH [CM]	STAND-OVER [IN]	TOP TUBE SLOPE	FORK RAKE [MM]	STACK	REACH
48	51.5	45.0	10.0	72.50	74.75	7.4	40.5	28.4	10.6	50	535	369
50	52.5	47.0	10.5	72.75	74.50	7.4	40.5	28.9	8.8	50	541	375
52	53.5	48.5	11.5	73.00	74.25	7.3	40.5	29.4	8.2	45	552	380
54	54.5	50.0	13.0	73.25	74.00	7.2	40.5	30.0	8.1	45	566	383
55	55.5	51.0	14.0	73.50	73.50	7.2	40.7	30.3	8.2	45	576	385
56	56.5	52.0	15.0	73.50	73.25	7.2	40.7	30.7	8.0	45	586	390
58	57.5	53.5	16.5	73.75	73.00	7.1	41.0	31.3	8.2	40	601	392
60	58.5	55.0	18.0	74.00	73.00	7.0	41.0	31.9	8.0	40	616	398
62	59.5	57.0	20.0	74.25	72.50	6.8	41.5	32.7	6.5	40	634	397

STANDOVER MEASURED WITH 23C TIRE / MAX TIRE WIDTH 28MM / STACK AND REACH INCLUDE CK INSET UPPER CUP AND RACE



VAMOOTS

FRAME SIZE [CM]	EFFECTIVE TOP TUBE [CM]	SEAT TUBE /C-T/ [CM]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB DROP [CM]	CHAIN STAY LENGTH [CM]	STAND-OVER [IN]	TOP TUBE SLOPE	FORK RAKE [MM]	STACK	REACH
48	51.0	48.0	10.5	71.50	74.75	8.0	41.0	28.8	7.9	50	542	362
50	52.0	50.0	11.0	72.00	74.50	8.0	41.0	29.3	6.3	50	549	368
52	53.0	52.0	12.0	72.00	74.25	7.8	41.0	29.9	4.8	50	557	373
54	54.0	54.0	14.0	72.25	74.00	7.8	41.5	30.7	4.8	50	577	375
55	55.0	55.0	15.0	72.50	73.50	7.6	41.5	31.1	4.9	50	586	377
56	56.0	56.0	16.0	72.75	73.25	7.6	41.5	31.5	5.0	50	597	381
58	57.0	58.0	17.0	72.75	73.00	7.6	42.0	32.1	3.9	50	606	385
60	58.0	60.0	19.0	73.00	72.50	7.2	42.0	32.9	3.7	45	623	385
62	59.0	62.0	21.0	73.00	72.50	7.2	42.0	33.6	3.6	45	642	389

STANDOVER MEASURED WITH 23C TIRE / MAX TIRE WIDTH 28MM / STACK AND REACH INCLUDE CK INSET UPPER CUP AND RACE



VAMOOTS DR

FRAME SIZE [CM]	EFFECTIVE TOP TUBE [CM]	SEAT TUBE /C-T/ [CM]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB DROP [CM]	CHAIN STAY LENGTH [CM]	STAND-OVER [IN]	TOP TUBE SLOPE	FORK RAKE [MM]	STACK	REACH
48	51.5	45.0	12.0	71.50	74.75	7.6	41.5	28.6	13.2	43	543	367
50	52.5	47.0	12.0	72.00	74.50	7.6	41.5	29.0	10.8	43	545	374
52	53.5	48.5	13.0	72.00	74.25	7.5	41.5	29.7	10.1	43	554	379
54	54.5	50.0	15.0	72.25	74.00	7.5	41.5	30.3	10.5	43	575	380
55	55.5	51.0	16.0	72.75	73.50	7.5	41.5	30.7	10.7	43	585	383
56	56.5	52.0	17.0	73.00	73.25	7.5	41.5	31.0	10.7	43	595	387
58	57.5	53.5	18.0	73.00	73.00	7.3	42.0	31.5	9.8	43	603	392
60	58.5	55.0	20.0	73.25	72.50	7.1	42.0	32.2	10.2	43	621	390
62	59.5	57.0	22.0	73.25	72.50	7.0	42.0	32.9	9.9	43	639	395

STANDOVER MEASURED WITH 23C TIRE / MAX TIRE WIDTH 29MM / STACK AND REACH INCLUDE CK INSET UPPER CUP AND RACE / DESIGNED FOR EXTERNAL LOWER CUP STOCK WITH 140MM POST MOUNT, ADAPTABLE TO 160



ROUTT + ROUTT YBB

FRAME SIZE [CM]	EFFECTIVE TOP TUBE [CM]	SEAT TUBE /C-T/ [CM]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB DROP [CM]	CHAIN STAY LENGTH [CM]	STAND-OVER [IN]	TOP TUBE SLOPE	FORK RAKE [MM]	STACK	REACH
50 RIG	51.5	46.0	12.0	70.75	75.00	7.1	42.3	30.0	14.2	47	562	365
50 YBB	51.5	50.5	12.0	70.75	75.00	7.1	43.0	30.8	8.6	47	562	365
52 RIG	52.5	48.0	14.0	71.00	74.25	7.1	42.3	31.0	14.3	47	582	361
52 YBB	52.5	50.5	14.0	71.00	74.25	7.1	43.0	31.2	9.8	47	582	361
54	54.0	51.0	15.0	71.50	74.00	6.9	42.3	31.6	11.6	47	591	371
55	55.0	52.0	16.0	71.50	73.50	6.9	42.3	31.9	11.5	47	601	373
56	56.0	53.0	17.0	72.00	73.25	6.9	42.3	32.4	11.0	47	612	377
58	58.0	55.0	18.0	72.00	73.00	6.9	42.3	32.8	10.6	47	621	391
60	59.5	57.0	20.0	72.50	72.75	6.8	42.3	33.7	10.1	47	642	397

STANDOVER MEASURED WITH 32C TIRE / MAX TIRE WIDTH 34MM / STACK AND REACH INCLUDE CK INSET UPPER CUP AND RACE / DESIGNED FOR EXTERNAL LOWER CUP



ROUTT 45

FRAME SIZE [CM]	EFFECTIVE TOP TUBE [CM]	SEAT TUBE /C-T/ [CM]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB DROP [CM]	CHAIN STAY LENGTH [CM]	STAND-OVER [IN]	TOP TUBE SLOPE	FORK RAKE [MM]	STACK	REACH
50 RIG	51.5	46.0	12.0	70.75	75.00	7.1	45.0	30.0	14.2	47	562	365
52	52.5	48.0	14.0	71.00	74.25	7.1	45.0	31.0	14.3	47	582	361
54	54.0	51.0	15.0	71.50	74.00	6.9	45.0	31.6	11.6	47	591	371
55	55.0	52.0	16.0	71.50	73.50	6.9	45.0	31.9	11.5	47	601	373
56	56.0	53.0	17.0	72.00	73.25	6.9	45.0	32.4	11.0	47	612	377
58	58.0	55.0	18.0	72.00	73.00	6.9	45.0	32.8	10.6	47	621	391
60	59.5	57.0	20.0	72.50	72.75	6.8	45.0	33.7	10.1	47	642	397

STANDOVER MEASURED WITH 32C TIRE / MAX TIRE WIDTH 41MM / STACK AND REACH INCLUDE CK INSET UPPER CUP AND RACE / DESIGNED FOR EXTERNAL LOWER CUP



PSYCHLO X RSL

FRAME SIZE [CM]	EFFECTIVE TOP TUBE [CM]	SEAT TUBE /C-T/ [CM]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB DROP [CM]	CHAIN STAY LENGTH [CM]	STAND-OVER [IN]	TOP TUBE SLOPE	FORK RAKE [MM]	STACK	REACH
50	52.5	48.0	11.0	71.50	74.50	6.3	42.3	30.5	10.1	47	547	373
52	53.5	52.0	12.0	72.00	74.00	6.3	42.3	31.5	6.7	47	558	376
54	55.0	54.0	13.0	72.50	73.50	6.1	42.3	32.0	5.5	47	568	383
55	56.0	55.0	14.0	72.50	73.50	6.1	42.3	32.4	5.4	47	577	390
56	57.0	56.0	15.0	72.50	73.00	6.1	42.3	32.8	5.4	47	587	392
58	58.5	58.0	16.0	73.00	73.00	6.1	42.3	33.4	4.4	47	598	403
60	60.0	60.0	18.0	73.00	72.50	6.0	42.3	34.1	4.3	47	616	406

STANDOVER MEASURED WITH 32C TIRE / MAX TIRE WIDTH 34MM / STACK AND REACH INCLUDE CK INSET UPPER CUP AND RACE / DESIGNED FOR EXTERNAL LOWER CUP STOCK WITH 140MM POST MOUNT, ADAPTABLE TO 160

ROAD

CROSS

SPECIFICATIONS

MOOTS

SPEC DEFINITIONS AND NOTES

All Road Bikes
STAND-OVER MEASURED WITH 23C TIRE

All CX Bikes
STAND-OVER MEASURED WITH 32C TIRE

All CX Bikes
DESIGNED WITH 44MM HEAD TUBE USING EXTERNAL LOWER BEARING HEAD SET COMPATIBLE WITH STRAIGHT AND TAPERED FORKS.

Effective Top Tube
MEASURED PARALLEL TO GROUND, FROM TOP OF HEAD TUBE CENTER TO SEAT TUBE CENTER

Seat Tube Length
CENTER OF BB TO TOP OF SEAT COLLAR

BB Drop
MEASURED FROM AXLE CENTER LINE TO BB CENTER

THE COMBINATION OF SOME FRAME SIZES, FOOT SIZE AND TIRE SIZES MAY RESULT IN TOE OVERLAP

MOOTS .COM

MOUNTAIN

SPECIFICATIONS

MOOTO X RSL 29"

FRAME SIZE [IN]	EFFECTIVE TOP TUBE [IN]	SEAT TUBE /C-T/ [IN]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB HEIGHT [IN]	CHAIN STAY LENGTH [IN]	STAND-OVER [IN]	FORK TRAVEL	STACK	REACH
16*	22.50	16.0	11.0	71.00	74.50	11.875	17.55	30.3	100mm	627	397
17	23.00	16.5	11.0	71.25	74.25	11.875	17.55	31.8	100mm	628	407
18	23.50	17.5	11.0	71.25	74.00	12.000	17.55	32.2	100mm	625	417
19	24.25	18.5	11.0	71.25	73.75	12.000	17.55	32.7	100mm	625	433
20	24.75	19.5	12.0	71.50	73.50	12.000	17.55	33.4	100mm	636	440
22	25.50	21.0	13.0	71.50	73.25	12.125	17.55	34.3	100mm	642	454

***Comes standard with curved top tube for greater stand-over**
STACK AND REACH INCLUDE CK INSET UPPER CUP AND RACE / DESIGNED FOR EXTERNAL LOWER CUP



ROGUE RSL 27.5"

FRAME SIZE [IN]	EFFECTIVE TOP TUBE [IN]	SEAT TUBE /C-T/ [IN]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB HEIGHT [IN]	CHAIN STAY LENGTH [IN]	STAND-OVER [IN]	FORK TRAVEL	STACK	REACH
14*	21.50	15.0	11.0	68.75	74.50	11.75	16.9	29.1	100mm	586	383
15*	22.00	15.0	11.0	69.00	74.50	11.75	16.9	29.1	100mm	587	395
16*	22.50	16.0	11.0	69.00	74.25	11.75	16.9	29.8	100mm	587	405
17*	23.00	17.0	11.0	69.00	74.25	12.00	16.9	30.1	100mm	584	419
18	23.50	18.0	12.0	69.50	74.00	12.00	16.9	31.9	100mm	596	425
19	24.25	19.0	13.0	69.50	74.00	12.00	16.9	32.5	100mm	605	442
20	24.75	20.0	14.0	70.00	73.75	12.25	16.9	33.3	100mm	610	450
22	25.50	22.0	15.0	70.00	73.75	12.25	16.9	34.4	100mm	620	467

***Comes standard with a curved top tube for greater stand-over**
STACK AND REACH INCLUDE CK INSET UPPER CUP AND RACE / DESIGNED FOR EXTERNAL LOWER CUP / 3RD H2O NOT AN OPTION ON 14-17" FRAMES



MOOTO X YBB 29"

FRAME SIZE [IN]	EFFECTIVE TOP TUBE [IN]	SEAT TUBE /C-T/ [IN]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB HEIGHT [IN]	CHAIN STAY LENGTH [IN]	STAND-OVER [IN]	FORK TRAVEL	STACK	REACH
16*	22.50	19.75**	11.0	70.50	74.50	11.875	18.1	29.7	100mm	625	398
17*	23.00	19.75**	11.0	70.75	74.25	12.000	18.1	30.0	100mm	623	408
18*	23.50	19.75	12.0	71.00	74.00	12.000	18.1	32.5	100mm	627	417
19*	24.25	20.0	12.0	71.25	73.75	12.125	18.1	32.6	100mm	631	432
20	24.75	20.25	13.0	71.50	73.50	12.125	18.1	33.9	100mm	642	438
22	25.50	22.0	14.0	71.50	73.25	12.250	18.1	35.1	100mm	648	452

***Comes standard with a curved top tube for greater stand-over **Seat tube uses strut**
STACK AND REACH INCLUDE CK INSET UPPER CUP AND RACE / DESIGNED FOR EXTERNAL LOWER CUP / 3RD H2O NOT AN OPTION ON 16 AND 17" FRAMES



ROGUE YBB 27.5"

FRAME SIZE [IN]	EFFECTIVE TOP TUBE [IN]	SEAT TUBE /C-T/ [IN]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB HEIGHT [IN]	CHAIN STAY LENGTH [IN]	STAND-OVER [IN]	FORK TRAVEL	STACK	REACH
14*	21.50	18.25**	11.0	68.75	74.50	11.800	17.4	29.0	100mm	586	383
15*	22.00	18.25**	11.0	69.00	74.50	11.800	17.4	29.0	100mm	587	395
16*	22.50	18.25**	11.0	69.00	74.25	11.875	17.4	29.0	100mm	587	405
17*	23.00	18.25	11.0	69.00	74.25	12.000	17.4	30.3	100mm	584	419
18*	23.50	18.5	12.0	69.50	74.00	12.000	17.4	31.0	100mm	596	425
19*	24.25	19.0	13.0	69.50	74.00	12.125	17.4	31.5	100mm	605	442
20	24.75	20.0	14.0	70.00	73.75	12.125	17.4	33.3	100mm	610	450
22	25.50	22.0	15.0	70.00	73.75	12.250	17.4	34.4	100mm	620	467

***Comes standard with a curved top tube for greater stand-over **Seat tube uses strut**
STACK AND REACH INCLUDE CK INSET UPPER CUP AND RACE / DESIGNED FOR EXTERNAL LOWER CUP / 3RD H2O NOT AN OPTION ON 14-17" FRAMES



MOOTO X 29"

FRAME SIZE [IN]	EFFECTIVE TOP TUBE [IN]	SEAT TUBE /C-T/ [IN]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB HEIGHT [IN]	CHAIN STAY LENGTH [IN]	STAND-OVER [IN]	FORK TRAVEL	STACK	REACH
16*	22.50	16.0	11.0	69.50	74.50	12.125	17.8	30.3	100mm	614	400
17	23.00	17.0	11.0	69.50	74.25	12.250	17.8	32.0	100mm	611	411
18	23.50	17.5	12.0	69.50	74.00	12.250	17.8	32.7	120mm	634	414
19	24.25	18.5	12.0	70.00	73.75	12.250	17.8	33.2	120mm	636	430
20	24.75	20.0	13.0	70.50	73.50	12.250	17.8	34.1	120mm	648	436
22	25.50	22.0	14.0	70.50	73.25	12.375	17.8	35.3	120mm	654	450

***Comes standard with a curved top tube for greater stand-over**
3RD H2O NOT AN OPTION ON 16" FRAME



MX DIVIDE 29"

FRAME SIZE [IN]	EFFECTIVE TOP TUBE [IN]	SEAT TUBE /C-T/ [IN]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB HEIGHT [IN]	CHAIN STAY LENGTH [IN]	STAND-OVER [IN]	FORK TRAVEL
16	22.50	17.0	10.0	70.50	74.00	13.0	17.8	30.8	100mm
17	23.00	17.0	11.0	70.50	74.00	13.0	17.8	30.9	100mm
18	23.50	17.5	12.0	71.00	74.00	13.0	17.8	30.9	100mm
19*	24.25	19.0	12.0	71.00	74.00	13.0	17.8	31.1	100mm
20*	24.75	19.5	13.0	71.50	74.00	13.0	17.8	31.1	100mm
22*	25.50	21.0	14.0	71.50	74.00	13.0	17.8	31.2	100mm

***Designed with top tube to seat tube strut**
STACK AND REACH INCLUDE CK INSET UPPER CUP AND RACE / DESIGNED FOR EXTERNAL LOWER CUP



FROSTHAMMER 5" TIRE

FRAME SIZE [IN]	EFFECTIVE TOP TUBE [IN]	SEAT TUBE /C-T/ [IN]	HEAD TUBE LENGTH [CM]	HEAD ANGLE	SEAT ANGLE	BB HEIGHT [IN]	CHAIN STAY LENGTH [IN]	STAND-OVER [IN]
16	22.0	16.0	11.0	69.00	74.00	12.1	17.85	29.7
18	23.5	17.0	12.0	69.00	74.00	12.1	17.85	30.4
20	24.5	19.0	14.0	69.00	73.00	12.1	17.85	31.7
22	25.5	21.0	16.0	69.00	73.00	12.1	17.85	33.0

Also available with optional 170 spacing as FrosTi
190MM REAR SPACING / ISO DISC REAR / REPLACEABLE HANGER / 100MM WIDE ENGLISH BB SHELL / DESIGNED FOR 483 MM AXLE TO CROWN FORK / CHAINLINE 76MM



MOOTS

SPEC DEFINITIONS AND NOTES

All Mountain Bikes
STAND-OVER MEASURED UNSAGGED WITH 2.2" TIRES

All YBB & Hardtail Bikes
ALL SPECS, EXCEPT STAND-OVER, MEASURED WITH 25% SAG

ALL FULL-SUSPENSION BIKE SPECS MEASURED UNSAGGED

Effective Top Tube
MEASURED PARALLEL TO GROUND, FROM TOP OF HEAD TUBE CENTER TO SEAT TUBE CENTER

Seat Tube Length
CENTER OF BB TO TOP OF SEAT COLLAR

BB Height
FROM FLAT GROUND TO CENTER OF BB WITH 2.2" TIRE

Stand-Over
MEASURED AT TOP TUBE MID-POINT, UNSAGGED

All Mountain Bikes
SOME FRAME SIZE/FORK MODEL COMBOS MAY CAUSE DOWN TUBE TO FORK CROWN INTERFERENCE

All Mountain Bikes
DESIGNED FOR USE WITH 160MM MAX DISC BRAKE ROTORS AND WITH SHIMANO 48.8MM CHAINLINE CRANKSETS

All Mountain Bikes
DESIGNED WITH 44MM HEAD TUBE USING TAPERED FORKS/ EXTERNAL LOWER BEARING HEAD SET

All Mountain Bikes
MAX TIRE 2.25"

MOOTS .COM

STANDARD & OPTIONAL FEATURES

S STOCK
O OPTION

*** WILL REQUIRE STANDARD CHAIN STAY + SEAT STAY**
† SOME SMALLER SIZES ONLY FIT 2 BOTTLES, PLEASE SEE GEOMETRY CHART

Please see Moots geometry tables for model/size specific details

See **MOOURL**

OM for stock cable routing descriptions

	MOUNTAIN									ROAD						
STANDARD & OPTIONAL FEATURES	**MX DIVIDE** 29″	**MOOTO X RSL** 29″	**MOOTO X YBB** 29″	**MOOTO X** 29″	**ROGUE RSL** 27.5″	**ROGUE YBB** 27.5″	**DIVIDE** 26″	**YBB** 26″	**RIGORMOOTIS** 26″	**VAMOOTS RSL**	**VAMOOTS CR**	**VAMOOTS**	**VAMOOTS DR**	**PSYCHLO X RSL**	**ROUTT + ROUTT YBB**	**ROUTT 45**
CUSTOM GEOMETRY		O	O	O	O	O		O	O	O	O	O	O	O	O	O
STOCK CABLE ROUTING	A3	A2	A1C	A1C	A2	A1C	A3	A1C	A1C	R1	R1	R1	R5A	C2H	C2H	C2H
INTERNAL ELECTRONIC ROUTING	O	O	O	O	O	O	O	O	O	O	O	O	O	O	O	O
SLIDER DROPOUT		O*	O	O	O*	O		O	O					O*	O	O
TRACK DROPOUT											O	O		O*	O	
ISO DISC BRAKE MOUNT		O	O	S	O	O		S	S					O	S	S
POST DISC BRAKE MOUNT	S	S	S	O	S	S	S	O	O				S	S	O	O
CANTI BRAKE MOUNT														O	O	O
PRESS FIT 30 BOTTOM BRACKET	S	S	O	O	S	O	S	O	O	S	O	O	O	S	O	O
ENGLISH THREADED BOTTOM BRACKET		O	S	S	O	S		S	S	O	S	S	S	O	S	S
44MM HEAD TUBE	S	S	S	S	S	S	S	S	S	O	O	O	S	S	S	S
1 1/8″ HEAD TUBE										S	S	S				
FENDER MOUNTS+RACK EYELETS		O	O	O	O	O		O	O		O	O	O	O	O	O
3RD H20†+PUMP PEG+CHAIN HANGER		O	O	O	O	O		O	O	O	O	O	O	O	O	O
S&S COUPLERS			O	O	O	O		O	O		O	O	O		O	O
DECAL COLOR OPTIONS		S	S	S	S	S		S	S	S	S	S	S	S	S	S
MONOSTAY SEAT STAYS		S	S	S	S	S		S	S				S	S	S	S
DROPPER POST ROUTING	O	O	O	O	O	O	O	O	O							
MOOTS REYNOLDS BUTTED TUBE SET										S				S		
MOOTS PI-TECH 3/2.5 TUBE SET	S	S	S	S	S	S	S	S	S		S	S	S		S	S
30.9 SEATPOST	S	S	S	S	S	S	S			S				S		
27.2 SEATPOST								S	S		S	S	S		S	S
TAPERED CHAIN STAYS		S			S					S				S		
REPLACEABLE DERAILLEUR HANGER	S	S	S	S	S	S	S	S	S		S	S	S	S	S	S
130MM REAR DROPOUT SPACING										S	S	S		O	O	O
135MM REAR DROPOUT SPACING	O	S	O	S	S	O	O	S	S				S	S	S	S
142 X 12 THRU-AXLE SPACING	S	O	S	O	O	S	S	O	O				O	O	O	O
TAPERED SEAT STAYS		S			S									S		

MOOTS

HANDCRAFTED IN STEAMBOAT SPRINGS, COLORADO, USA, SINCE 1981